



Features

- User management
- Password protection
- Backup & Restore function
- Coordinate transformation
- Flexible result conjunction



general data

resolution	752 × 480 px
sensor type	1/3" CMOS, monochrome
illumination	integrated, LED white
LED class	risk group 1 (low risk, EN 62471:2008)
high-resolution mode	max. 50 inspections per second
high-speed mode (limited resolution)	max. 100 inspections per second
lens	16 mm
object distance min.	70 mm
number of jobs (products)	≤ 255
features per job	32
defect image memory	32
signal processing	Baumer FEX® 4.0

electrical data

voltage supply range +Vs	18 ... 30 V DC
power consumption	typical 5 W ($I_{max} = 1$ A at 24 V)
inputs	8 ... 30 V
outputs	PNP 100 mA
digital inputs	trigger job selection external teach-in encoders (CH-A, CH-B) 500 kHz
digital outputs	Pass / Fail 1-5 Flash Sync Alarm Camera Ready Output Enable
initial setup	Ethernet (10BASE-T / 100BASE-TX)
process interface	TCP UDP (Ethernet)
visualization	web interface

mechanical data

width	53 mm
height	99,5 mm
depth	38 mm
material	housing: aluminum cover glass: PMMA
weight	≤ 250 g

environmental conditions

operating temperature	+5 ... +50 °C
storage temperature	-20 ... +70 °C
case temperature	max. +50 °C
humidity	0 ... 90 % (non-condensing)
protection class	IP 67
vibration load	IEC 60068-2-6 IEC 60068-2-27
mechanical shock resistance	EN 60068-2-27

code types

barcode	2/5 Industrial
	2/5 Interleaved
	Codabar
	Code 39
	Code 93
	Code 128
	PharmaCode
	EAN 8
	EAN 13
	UPC-A
UPC-E	
GS1 DataBar	
GS1 128	
matrix code	DataMatrix (ECC 200)
	GS1-DataMatrix
	QR-Code
	PDF417

code types

font many font styles (recommended: sans serif, proportional)
Dot Matrix
characters: A-Z a-z 0-9 + - . : / ()

feature checks

part location part location on contours
part location on edges
part location on circle
part location on text line

geometry distance
circle
angle
count edges
point position

feature comparison count contour points
contour comparison
brightness
contrast
area size
count areas
pattern comparison

identification barcode
matrix code
text

electrical connection M12 / 12-pin (on device)



1: PWR (+18-30 V DC)	7: OUT3
2: Ground	8: IN3
3: IN1 (Trigger)	9: OUT4
4: OUT1	10: IN4
5: IN2	11: IN5
6: OUT2	12: OUT5

Ethernet connection M12 / 4-pin (on device)



1: TD+	3: TD-
2: RD+	4: RD-

dimension drawing

